

**Permeable Paving Grid System** 

PROPERTIES	CHARACTERISTICS	REF
	OCity PAV65	
Material	Polyethylene PE	
Mass per unit	7.5 kg per SQM	ISO 845
Length	500 mm	
Width	500 mm	
Good Coverage	0.25 SQM per grid	ISO 1923
Grid Thickness	65 mm	
Wall Thickness	6 - 10mm	
Grid weight	approx. 1.9 kg per grid	
	approx 7.6 kg per SQM	
Colour	Black	
Anchoring	4 interlocking points per side	
Paving Fill Material	Concrete block pavers	
Paving Fill Dimensions	150mm x 150mm x 60mm	
Paving Fill Quantity	9 block pavers per grid	
	36 block pavers per SQM	
Chemical Properties	High resistance to water, most acids, bases and salt solutions	
UV Resistance	Anti UV treatment	

MECHANICAL PROPERTIES		
Compression Resistance*	up to 800 tonnes per SQM	ISO 844
Applications**	Areas for pedestrians, cyclist and motorcyclists	
	Light vehicle driveways (up to 7.5 ton HGV)	ISO 124
	Light vehicle parking areas (up to 7.5 ton HGV)	

\*Variation subject to nature of the concrete block paver infill

\*\*The values indicated on this technical data sheet serve may be used as guidelines for product use. They should be considered neither a specification limits, nor as guarantees. In addition, product application, use and/or processing are beyond our control and consequently, they remain the responsibility of the user and/or the transformer.




## www.nidagraveluk.co.uk

Nidagravel UK | Gravel Stabilisers UK Ltd 4 Thorpe Court, Thorpe Waterville, Northamptonshire NN14 3ED T: 01832 77 65 68 E: sales@nidagraveluk.co.uk



**Permeable Paving Grid System** 

## DIMENSIONAL DIAGRAMS








Nidagravel UK | Gravel Stabilisers UK Ltd 4 Thorpe Court, Thorpe Waterville, Northamptonshire NN14 3ED T: 01832 77 65 68 E: sales@nidagraveluk.co.uk

## Product ID OCity PAV65 Technical Data Sheet

## **Permeable Paving Grid System**



Concrete block paving infill 9 block pavers per grid Male / Female connectors 4 per side of each grid

100	2 2 h H K COM
A CONTRACTOR OF	A CONTRACTOR
The second s	
and the second se	
1 H 1 H 1 H 1 H 1	
the second se	
and the second second	
ALC: NOT THE OWNER OF THE OWNER O	
A CONTRACTOR OF	and the second second second
A CONTRACTOR OF	and the second se
ALC: NOT THE OWNER OF THE OWNER	
	and the second second second
1.1.2.2.2.2.2.2	
ALC: NOT A REAL PROPERTY OF	and the second se
ALC: NOT THE OWNER OF THE	and the second second second
the second se	
THE OWNER WAS DON'T DON'T	
THE REAL PROPERTY AND ADDRESS OF ADDRES	
	and the second se
	Sector Sector Sector
the second second second	
	and a set of the set of
	14.
	and the second
CALLS IN CALLS	and the second second
The second se	
And and a state of the state of	
and the second s	
and the second se	-

	OCity PAV65
QTY per pallet	140 Grids (max.)
SQM per pallet	35 SQM (max.)
Pallet Weight	280 kg (approx.)
Pallet Height	2200 mm
Pallet Length	1200 mm
Pallet Width	1000 mm
Pallet Material	Wooden (non-returnable)
Packaging	Shrink Wrapped & Banded
Pallet Unloading	Tail Lift / Manual Pallet Truck





Nidagravel UK | Gravel Stabilisers UK Ltd 4 Thorpe Court, Thorpe Waterville, Northamptonshire NN14 3ED T: 01832 77 65 68 E: sales@nidagraveluk.co.uk